


- Instruction:
- 1.Type:Film to Glass
 - 2.Operating Voltage:≤10V
 - 3.Response Time:≤10ms
 - 4.Storage Temperature: -20℃~+70℃
 - 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
 - 6.Hitting Life:>1,000,000 Times ,250gf Force;
 - 7.writing Life>1,000,000 Times 250gf Force;
 - 8.Connect Material:FP-C+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: ≥73%
- 12.Force: 100g or more
- 13.Linearity: ≤5%
14. Insulation: ≥20MΩ
15. Resistance: 50Ω<PIN1, PIN2<250Ω
50Ω<PIN4, PIN6<250Ω
50Ω<PIN3, PIN5<250Ω
50Ω<PIN7, PIN11<250Ω
- 16.Surface Hardness ≥3H(pencil)

Front ITO Film 0.188mm
hard coating anti newton ring
Back Glass—1.8mm

总厚度: 2.3 ± 0.15



Touch-Pane-VTW5191A0

REVISIQNS

SCALE	1:1	MATERIAL	F/0	Version	1.0
UNIT	mm	TOLERANCE	±0.3mm		
DESIGN	Jaka	DATE	20090506		
CHECK	patric * 11	DATE	20090506		
RELEASE	J	DATE	20090506		