


注 (NOTE) :

- 有效触摸区尺寸: 477×268
Active Area Dimensions: 477×268
可视区尺寸: 477×268
Viewable Area Dimensions: 477×268
外形尺寸: 526×317
Outline Dimensions: 526×317
 - 部件说明 (PARTS SPECIFICATION):
 - ① 工艺孔 (Technics Hole)
 - ② 防尘框, 材料: 铝合金 (Dust-proof Frame, Material: Aluminum)
 - ③ 触摸屏体, 厚度: 4 (Touch-panel, Thickness: 4)
 - ④ 屏线, 直径6 (Data Cable, $\phi 6$)
 - ⑤ 接地线。 (Ground Cable)
 - ⑥ 屏线插头 (Housing Of Data Cable)
3. 所有尺寸为设计尺寸, 单位是mm, 未注公差为 ± 0.5 。
All dimensions are in millimeters, the unspecified dimension tolerances are plus/minus 0.5



I Direction		I Direction	
PIN	Signal	Insulation Color	Overall Shield
1	Overall Shield		
2	Y + Receive	BLUE	
3	Y + Receive	BLUE	
4	Y Transmit	BLUE	
5	Y - Receive	BLACK	
6	Y Ground	YELLOW	
7	Shield		
8	X Ground	GREEN	
9	X+Receive	WHITE	
10	X Transmit	RED	
11	X-Receive	RED	
12			

Unmarked Tolerance		Shenzhen Keetouch Electronic Co., Ltd	
From (mm)	To (mm)	product	Drawing No.
0	10	Shenzhen Keetouch Electronic Co., Ltd	KAL-0215-4BP-169AL
10	50	Specs	Revision
50	100	Drawing/Date	16/02/07-6
		Check/Date	
		Approve/Date	
		Scale	1:1
		Shadow	
100%以上		Total X I P X I P	